PLL & UHF **ANTENNA DIVERSITY SINGLE CHANNEL SYSTEM**

SYSTEM FEATURES

- * 8 Selectable UHF channel
- Adopt PLL-Synthesized control technic
- LED information display
- * Balanced XLR and unbalanced 1/4" outputs



PAGE-06

WR-25 SERIES >>>

WR-25







RECEIVER SPECIFICATIONS

HEDELVEH OF EOH TOATTONG	
RF Frequency Range:460-970MHz	
Image & Squrious Rejection:>70dB	
Receiving Sensitivity:-105dBm	
Signal/Noise Ratio:-105dB	
Border Upon Channel Rejection>70dB	
T.H.D.:<1%	
Audio Output Level:0-300mV	
Power Requirements:13-15V DC nominal 300mA	
Dimensions:17.5x13.5x4.3cm	

HANDHELD TRANSMITTER SPECIFICATIONS RF Frequency Range:460-970MHz RF Output:>10dBm Modulation Type:FM Max Deviation: ±40KHz

PAGE-07

Spurious Emission:>55dBc Nominal Current Drain: < 40mA Power Requirements: 2x1.5V AA HT-25 Dimensions:23.5x5x5cm

HT-25A Dimensions:25x5.1x5.1cm

RF Frequency Range:460-970MHz RF Output:>10dBm Modulation Type:FM Max Deviation: ±40KHz Spurious Emission:>53dBc Nominal Current Drain: < 40mA

BODYPACK TRANSMITTER SPECIFICATIONS


Power Requirements: 2x1.5V AA Dimensions:10.5x6.5x3cm

HANDHELD





HEADWORN Receiver:WR-25 Bodypack Transmitter: PT-25 Headworn Mic: HT-9A



GUITAR/BASS Receiver: WR-25 Bodypack Transmitter: PT-25 Guitar Cable: G-05

