

# UHF TRUE DIVERSITY SINGLE CHANNEL SYSTEM

## SYSTEM FEATURES

- ※ UHF 800MHz operation frequency
- ※ True diversity single channel operation.
- ※ Extreme low THD and super fidelity
- ※ Switch impact noise defeat circuit
- ※ Double squelch operation circuit, higher efficient and much more steady.
- ※ Balanced XLR and unbalanced 1/4" outputs.
- ※ EIA standard half rack metal housing with rack ear.



**KLT-9U**  
BODYPACK TRANSMITTER  
Top View

**KST-3U**  
HANDHELD TRANSMITTER

**KST-5U**  
HANDHELD TRANSMITTER

**KRU-211**  
TRUE DIVERSITY RECEIVER



Rear Panel



19-inch Audio equipment rack

# KRU-211 1 SERIES >>>

PROFESSIONAL WIRELESS MICROPHONE SYSTEM

KRU-211	KST-3U/KST-5U	KLT-9U
<b>RECEIVER SPECIFICATIONS</b>	<b>HANDHELD TRANSMITTER SPECIFICATIONS</b>	<b>BODYPACK TRANSMITTER SPECIFICATIONS</b>
RF Frequency Range:460-970MHz	RF Frequency Range:460-970MHz	RF Frequency Range:460-970MHz
Frequency Stabilization:10PPM	Frequency Stabilization:10PPM	Frequency Stabilization:10PPM
Receiving Sensitivity:-107dB	RF Output Power:10dBm	RF Output Power:10dBm
RF Image Spurious Rejection:>75dB	RF Spurious Emission:>60dBc	RF Spurious Emission:>60dBc
Border Upon Channel Rejection:>90dB	Max Deviation:>40KHz	Max Deviation:>40KHz
Power Requirements:13-15V DC nominal 300mA	Battery Voltage:9V DC	Battery Voltage:9V DC
Dimensions :21x22.1x4.5cm	Max Drain at 9V DC:<38mA	Max Drain at 9V DC:<38mA
	KST-3U Dimensions:24x5x5cm	Dimensions:8.2x6x2.3cm
	KST-5U Dimensions:23.5x5x5cm	

### HANDHELD

Receiver:KRU-211  
Handheld Mic:KST-3U or KST-5U

### LAVALIER

Receiver:KRU-211  
Bodypack Transmitter:KLT-9U  
Lavalier Mic:LT-4C

### HEADWORN

Receiver:KRU-211  
Bodypack Transmitter:KLT-9U  
Headworn Mic: HT-1C

### GUITAR/BASS

Receiver:KRU-211  
Bodypack Transmitter:KLT-9U  
Guitar Cable:G-05C