

UHF DUAL CHANNEL SYSTEM

SYSTEM FEATURES

- ※ UHF 800MHz operation frequency
- ※ Dual channel operation
- ※ Extreme low THD and super fidelity
- ※ Switch impact noise defeat circuit
- ※ Double squelch operation circuit, higher efficient and much more steady.
- ※ Balanced XLR and unbalanced 1/4" outputs.
- ※ EIA standard half rack metal housing with rack ear.



KLT-9U
BODYPACK TRANSMITTER
Top View

KRU-212
DUAL CHANNEL RECEIVER
19-inch Audio equipment rack

Rear Panel

KST-3U
HANDHELD TRANSMITTER
OR
KST-5U
HANDHELD TRANSMITTER

KRU-212 SERIES >>>

PROFESSIONAL WIRELESS MICROPHONE SYSTEM

KRU-212	KST-3U/KST-5U	KLT-9U
RECEIVER SPECIFICATIONS	HANDHELD TRANSMITTER SPECIFICATIONS	BODYPACK TRANSMITTER SPECIFICATIONS
RF Frequency Range:460-970MHz	RF Frequency Range:460-970MHz	RF Frequency Range:460-970MHz
RF Frequency Stabilization:10PPM	Frequency Stabilization:10PPM	Frequency Stabilization:10PPM
Receiving Sensitivity:-107dB	RF Output Power:10dBm	RF Output Power:10dBm
RF Image Spurious Rejection:>75dB	RF Spurious Emission:>60dBc	RF Spurious Emission:>60dBc
Border Upon Channel Rejection:>90dB	Max Deviation:>40KHz	Max Deviation:>40KHz
Power Requirements:13-15V DC nominal 300mA	Battery Voltage:9V DC	Battery Voltage:9V DC
Dimensions :21x22.1x4.5cm	Max Drain at 9V DC:<38mA	Max Drain at 9V DC:<38mA
	KST-3U Dimensions:24x5x5cm	Dimensions:8.2x6x2.3cm
	KST-5U Dimensions:23.5x5x5cm	

HANDHELD

Receiver:KRU-212
Handheld Mic:KST-3U or KST-5U

LAVALIER

Receiver:KRU-212
Bodypack Transmitter:KLT-9U
Lavalier Mic:LT-4C

HEADWORN

Receiver:KRU-212
Bodypack Transmitter:KLT-9U
Headworn Mic: HT-1C

GUITAR/BASS

Receiver:KRU-212
Bodypack Transmitter:KLT-9U
Guitar Cable:G-05C

DUAL CHANNEL COMBO

Receiver:KRU-212
Handheld Mic:KST-3U or KST-5U
Bodypack Transmitter:KLT-9U
Lavalier Mic:LT-4C
Headworn Mic: HT-1C
Guitar Cable:G-05C