

UHF DUAL CHANNEL SYSTEM

SYSTEM FEATURES

- ※ UHF 800MHz operation frequency
- ※ Dual channel operation
- ※ Extreme low THD and super fidelity
- ※ Switch impact noise defeat circuit
- ※ Double squelch operation circuit, higher efficient and much more steady.
- ※ Balanced XLR and unbalanced 1/4" outputs.



KRU-302 SERIES >>>

PROFESSIONAL WIRELESS MICROPHONE SYSTEM

KRU-302



RECEIVER SPECIFICATIONS

RF Frequency Range:460-970MHz
Receiving Sensitivity:-105dBm(S/N:-12dB 25KHz)
Image & Spurious Rejection:>70dB
Signal/Noise Ratio:>85dB
Border Upon Channel Rejection:>70dB
T.H.D.:<0.5%
Audio Output Level:0- ± 300mV
Power Requirements:13-15V DC nominal 300mA
Dimensions:21.3x15x4.3cm

KST-5U



HANDHELD TRANSMITTER SPECIFICATIONS

RF Frequency Range:460-970MHz
RF Output:10dBm
Modulation Type:FM
Max Deviation: ± 40KHz
Spurious Emission:>55dBc
Nominal Current Drain:<40mA
Power Requirements:9V DC
Dimensions:23x5x5cm

KLT-8U



BODYPACK TRANSMITTER SPECIFICATIONS

RF Frequency Range:460-970MHz
RF Output:10dBm
Modulation Type:FM
Max Deviation: ± 40KHz
Spurious Emission:>53dBc
Nominal Current Drain:<40mA
Power Requirements:9V DC
Dimensions:10.5x6.5x2.5cm

HANDHELD



LAVALIER



HEADWORN



GUITAR/BASS



DUAL CHANNEL COMBO

