

# UHF SINGLE CHANNEL SYSTEM

## SYSTEM FEATURES

- ※ UHF 800MHz operation frequency
- ※ Single channel operation
- ※ Balanced XLR and unbalanced 1/4" outputs



# WR-9 SERIES >>>

PROFESSIONAL WIRELESS MICROPHONE SYSTEM

WR-9	HT-15/HT-15A	PT-15
<b>RECEIVER SPECIFICATIONS</b> RF Frequency Range:460-970MHz Image & Scurious Rejection:>70dB Receiving Sensitivity:-105dBm Signal/Noise Ratio:-105dB Border Upon Channel Rejection>70dB T.H.D.:<1% Audio Output Level:0-300mV Power Requirements:13-15V DC nominal 200mA Dimensions:16.9x12x3.7cm	<b>HANDHELD TRANSMITTER SPECIFICATIONS</b> RF Frequency Range: 460-970MHz RF Output: >10dBm Modulation Type: FM Max Deviation: ±40KHz Spurious Emission: >55dBc Nominal Current Drain:<40mA Power Requirements: 2x1.5V AA HT-15 Dimensions: 23.5x5x5cm HT-15A Dimensions:25x5.1x5.1cm	<b>BODYPACK TRANSMITTER SPECIFICATIONS</b> RF Frequency Range: 460-970MHz RF Output: >10dBm Modulation Type: FM Max Deviation: ±40KHz Spurious Emission: >53dBc Nominal Current Drain: <40mA Power Requirements: 2x1.5V AA Dimensions: 10.5x6.5x3cm

<b>HANDHELD</b>  Receiver: WR-9 Handheld Mic: HT-15/HT-15A	<b>LAVALIER</b>  Receiver: WR-9 Bodypack Transmitter: PT-15 Lavalier Mic: LT-4A
<b>HEADWORN</b>  Receiver: WR-9 Bodypack Transmitter: PT-15 Headworn Mic: HT-9A	<b>GUITAR/BASS</b>  Receiver: WR-9 Bodypack Transmitter: PT-15 Guitar Cable: G-05